

## NATURWAX ECO

### PROTECTIVE FINISHES



#### PRODUCT DESCRIPTION

- Description** Natural protective wax for spatulates and decorative Plasters.
- Intended use** Indoors  
Ideal for polishing decorations, it nourishes and regenerates the surfaces on which it is applied.
- Main features**
- Protective product based on natural waxes in aqueous dispersion
  - Creates a pleasant surface softness characterised by a pleasant scent

#### Main technical data

Technical information	Method	Main data at 20°C and 60% of R.H.
Appearance and finish		Opalescent paste
Consumption per coat	ISO 7254	35 ÷ 45 gr/m <sup>2</sup>

**Available colours** White.

#### LAYING

- Dilution and preparation of the product** Ready to use; it is possible to dilute it with water.  
If the product is too fluid (typical in summer) it is advisable to make it denser in a very cool place such as in a cold room.  
Stir thoroughly before application.
- Application tools** Application with a soft cloth, brush or spatula.  
Soft cloth polishing.
- Preparation of the substrate** DECORATED SURFACES  
The decorative effect to be protected must be perfectly seasoned and clean without any flaking parts, oils, greases and rising damp.
- Application system**
- Spread a generous amount of product over the entire surface to be treated using a soft cloth, brush or spatula
  - Uniform the application by distributing the product evenly, taking care to remove any excesses
  - Approximately 20÷30 minutes after application, polish the treated surface with a soft cloth

- Dust dry: 1-2 h
- Ready for polishing: after 20÷30 min

### Conditions of application

- The substrate must be dry, free from rising damp, dust, flaking and greasy parts
- New finishes must be perfectly dry and seasoned
- Ambient and substrate temperature: min. +10°C / max. +35°C in the first 24 hours after application
- Relative humidity of the environment: < 70%
- Substrate humidity: < 10% of R.H.

### Practical advice

- Do not apply the product during hours when the surfaces are exposed to direct sunlight, on a hot wall or in the presence of strong drafts
- Excess material can cause uneven effects and/or whitish halos
- Store the product in its original container, tightly closed and protected against frost and sun, at a temperature between +5°C and +35°C

### Known incompatibilities

None.  
For any use other than that indicated in this technical data sheet, contact our Technical Assistance Service.

### Cleaning of tools

With hot soapy water immediately after use.

### Safety Precautions

- Close the jar immediately after use
- Keep the container tightly closed after use, with the product undiluted, away from heat sources, away from frost and direct sunlight
- The safety information for the user is contained in the relevant safety data sheet
- Empty containers or containers with slight traces of dried film of residual product must be disposed of in compliance with local regulations

### Warnings

None.

## OTHER INFORMATION

### VOC classification (Directive 2004/42/EC)

Not envisaged.

### Other technical information

Technical information	Method	Main data at 20°C and 60% of R.H.
Density	ISO 2811-1	approx. 0.870 g/ml
Viscosity		approx. 800 cps

		(at 23°C)
Solid content		approx. 25.5 %
Flash point	UNI 8909	Non-flammable
Storage life	UNI 10154	At least 24 months

## ITEM SPECIFICATIONS

Application of NATURWAX ECO, natural protective wax, specifically designed for use on spatulated finishes and lime-based and synthetic Stuccoes such as Veneziano.

NATURWAX ECO is applied with a brush or soft cloth, or with a spatula, with an indicative consumption of 35÷45 gr/m<sup>2</sup>, depending on the absorption of the substrate.

Price on site € \_\_\_\_\_ per m<sup>2</sup> including materials, labour and excluding scaffolding, protections and any surface preparation.

All the technical indications contained herein are the result of our best experience, are indicative and do not constitute a guarantee of results. The data and methods shown on this technical data sheet can be modified at any time depending on any change in production technologies. The application of the products takes place outside our control and therefore falls under the sole responsibility of the customer. The correct use of the materials assumes compliance with the general requirements for use set out in the GENERAL CONSIDERATIONS page of the PRODUCT INFORMATION SHEETS collection and in particular with what is indicated in this sheet, especially with regard to the preparation and suitability of the supports. The technical service of Cromology Italia spa is available to users to provide additional information to that reported here. THIS DATA SHEET REPEALS AND REPLACES ANY PREVIOUS EDITION.

**CROMOLOGY ITALIA SpA ORGANISATION WITH QUALITY, SAFETY AND ENVIRONMENTAL MANAGEMENT SYSTEM ISO 9001, OHSAS 18001, ISO 14001 CERTIFIED BY BUREAU VERITAS SpA.**

**FOR PROFESSIONAL USE**