

OLTRE BASE

FLOOR SYSTEM

OLTRE

BEYOND BOUNDARIES

PRODUCT DESCRIPTION

Description Styrene acrylic binder-based primer, for user before bonding various finishes or applying decorative plasters.

Intended use Indoors

- Ultra-smooth concrete wall surfaces
- Fibre cement panels
- Plasterboard panels
- Ceramic tiles

Main features

- Increase the roughness of the substrate
- Increases the waterproofing of the substrate
- Consolidates any flaking parts of the substrate
- Ready to use

Main technical data

Technical information	Method	Main data at 20°C and 60% of R.H.
Adherence	EN ISO 4624	≥2 MPa
Average theoretical consumption	ISO 7254	100 ÷ 150 g/m ²

Available colours Blue

LAYING

Dilution and preparation of the product

- Application with brush: ready to use
- Application with roller: ready to use

Application tools

- Brush: soft synthetic bristles
- Roller: medium-short pile

Preparation of the substrate

Newly applied plaster must be left to cure for at least 4÷6 weeks to allow for the completion of natural carbonation. Any repairs should be left to cure properly.

Always clean the surface of any dust or other substances that could prevent the penetration of the product, such as oil or grease residue.

Old paint must be cohesive and adherent. If not, it should be removed completely.

WARNING: apply on perfectly dry substrates.

For all other application information or technical tips, please refer to the "Oltre" Decorative System Technical Manual.

Application system

- Shake well before use, apply BASE with a brush or roller in a single coat on one surface. Apply without interruption from one side to another
- Touch dry: max 2 h
- Dry in depth: max 24 h
- Over-painting: 4 -24 h

Conditions of application

- Ambient and substrate conditions: the substrate must be dry, free from dust and grease
- Ambient temperature: min. +10°C / max. +35°C
- Relative humidity of the environment: < 75%
- substrate humidity: < 10 of R.H.

Known incompatibilities

None.

For any use other than that indicated in this technical data sheet, contact our Technical Assistance Service

Cleaning of tools

Wash with water immediately after use.

Safety Precautions

- Keep the can tightly closed and protected against frost
- The safety information for the user is contained in the relevant safety data sheet
- Empty containers or containers with slight traces of dried film of residual product must be disposed of in compliance with local regulations

Warnings/Practical advice

- Close the jar immediately after use
- Store the product in the original packaging at room temperature between +5°C and +25°C
- Protect from frost!

OTHER INFORMATION

VOC classification (Directive 2004/42/EC)

Primer.

EU limit value for VOCs for BASE (cat. A/g): 30 g/L (2010). BASE contains a maximum of 2 g/L of VOC.

Other technical information

Technical information	Method	Main data at 20°C and 60% of R.H.
Density	ISO 2811-1	1.0÷1.1 g/ml
Permeability to water in liquid state	EN 1062-3	<0,1 kg/m ² h ^{0.5}
Storage life	UNI 10154	At least 12 months

ITEM SPECIFICATIONS

Apply **BASE** in the aqueous stage based on styrene-acrylic resins. **BASE** is applied with a brush or roller with a consumption of about 100 ÷ 150 g/m².

Price on site € _____ per m² including materials, labour and excluding scaffolding, protections and any surface preparation.

All the technical indications contained herein are the result of our best experience, are indicative and do not constitute a guarantee of results. The data and methods shown on this technical data sheet can be modified at any time depending on any change in production technologies. The application of the products takes place outside our control and therefore falls under the sole responsibility of the customer. The correct use of the materials assumes compliance with the general requirements for use set out in the GENERAL CONSIDERATIONS page of the PRODUCT INFORMATION SHEETS collection and in particular with what is indicated in this sheet, especially with regard to the preparation and suitability of the supports. Cromology Italia spa offers technical support to users who require any further information in addition to the data provided herein.

THIS DATA SHEET REPEALS AND REPLACES ANY PREVIOUS EDITION.

CROMOLOGY ITALIA SpA ORGANISATION WITH QUALITY, SAFETY AND ENVIRONMENTAL MANAGEMENT SYSTEM ISO 9001, OHSAS 18001, ISO 14001 CERTIFIED BY BUREAU VERITAS SpA.

PROFESSIONAL USE ONLY